

CCTV ANALOGIC/HD-TVI

PRODUS	IMAGINE	REZOLUTIE	DESCRIERE PRODUS	Pret Ron cu TVA
BU4-IRF4-4X		PAL	IR bullet camera ; 1/3" SONY Super HAD II CCD; NextChip DSP; Rezolutie:752 (H) x 582 (V), approx. 440k; 540 Linii TV; Lentila 3.6 mm; 24 IR LED, min.15m ; Filtru IR Cut Dual-Band; AGC; BLC; AWB; ATR: DNR-2D; IP66; IK10; Carcasa aluminiu; Cablu prin suport 3 axe; 12VDC max.3W; -30°C~+50°C; 171 x 62 x 65 mm	112
DS-2AE4225TI-D		2MP	HD1080p + CVBS; Speed Dome Exterior cu IR ; 3D DNR, D WDR; 1/2.8" Progressive Scan CMOS, 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 25x; Zoom digital: 16x; Lentila: 4.8-120mm ; Pan Manual Speed: 0.1°-80°/s; Pan Preset Speed: 80°/s; Tilt Manual Speed: 0.1°-80°/s; Tilt Preset Speed: 80°/s; Distanța IR: 100m, ajustabila de zoom ; IP66; Dimensiuni: Φ164.5x295mm; Greutate: 2 kg SURSA 12VDC si SUPORT DS-1602ZJ INCLUDE	1419
DS-2AE5223T-A3		2MP	HD1080p + CVBS; Speed Dome Interior ; 3D DNR, D WDR; 1/2.8" Progressive Scan CMOS, 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 25x; Zoom digital: 16x; Lentila: 4.8-120mm ; Pan Manual Speed: 0.1°-120°/s; Pan Preset Speed: 120°/s; Tilt Manual Speed: 0.1°-80°/s; Tilt Preset Speed: 80°/s; Dimensiuni: Φ183.4x243mm; Greutate: 3 kg SURSA 24VAC INCLUSA	1390
DS-2AE5225TI-A		2MP	HD1080p + CVBS; Speed Dome Exterior cu IR ; 3D DNR, D WDR; 1/2.8" Progressive Scan CMOS, 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 25x; Zoom digital: 16x; Lentila: 4.8-120mm ; Pan Manual Speed: 0.1°-120°/s; Pan Preset Speed: 120°/s; Tilt Manual Speed: 0.1°-80°/s; Tilt Preset Speed: 80°/s; Distanța IR: 150m, ajustabila de zoom; IP66; Dimensiuni: Φ208x305mm; Greutate: 3.3 kg SURSA 24VAC si SUPORT DS-1602ZJ INCLUDE	1484
DS-2AE7232TI-A		2MP	HD1080p; Speed Dome Exterior cu IR ; 3D DNR, D WDR; 1/2.8" Progressive Scan CMOS, 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 32x; Zoom digital: 16x; Lentila: 4.8-153mm ; Pan Manual Speed: 0.1°-160°/s; Pan Preset Speed: 160°/s; Tilt Manual Speed: 0.1°-120°/s; Tilt Preset Speed: 120°/s; Distanța IR: 150m, ajustabila de zoom ; IP66; Dimensiuni: Φ220x353.4mm; Greutate: 4.5 kg SURSA 24VAC si SUPORT DS-1602ZJ INCLUDE	2342
NOU DS-2CC52H1T-FITS		5MP	FISHEYE TURBO HD, 5 Megapixel high-performance CMOS, 2592 x 1944 @ 12.5fps , LED Array EXIR, 10-20m IR, Microfon incorporat , ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron) , Lentila FishEye 1.1 mm; DC 12V/max. 5.5W	676
DS-2CE16C0T-IT5		1MP	TURBO HD, 1 Megapixel CMOS, LED Array EXIR, 80m IR, Bullet, ICR, 0.1 Lux/F1.2, Smart IR, IP66, Interval mare al temperaturii de functionare (-40°~60°), Lentila 3,6 mm; DC 12V/max. 5W	112
DS-2CE16D0T-IRF		2MP	4in1, 2 Megapixel High Performance CMOS, 24 LEDuri IR, 20m IR, Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, IP66, Lentila 2.8 mm; DC 12V/max. 4W iesire TVI/AHD/CVI/CVBS selectabila	101
DS-2CE16D0T-IT3F		2MP	4in1, 2 Megapixel High Performance CMOS, LED Array EXIR, 40m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, IP66, Lentila 2.8 mm; DC 12V/max. 4W iesire TVI/AHD/CVI/CVBS selectabila	126
DS-2CE16D0T-IT5F		2MP	4in1, 2 Megapixel High Performance CMOS, LED Array EXIR, 80m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, IP66, Lentila 3.6mm; DC 12V/max. 4,5W Disponibila si cu lentila de 6 mm iesire TVI/AHD/CVI/CVBS selectabila	138
DS-2CE16D8T-IT		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 20m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila 2.8 mm; DC 12V/max. 4W	149

DS-2CE16D8T-IT3		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron), 120dB WDR , IP67, Lentila 2.8 mm; DC 12V/max. 5W	169
DS-2CE16D8T-IT3Z		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron), 120dB WDR , IP67, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 6W	268
DS-2CE16D8T-IT5		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 80m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron), 120dB WDR , IP67, Lentila 3,6 mm; DC 12V/max. 6W Disponibila si cu lentila de 6 mm	189
DS2CE16D9T-AIRAZH		2MP	TURBO HD, 2 Megapixel high-performance CMOS, LED Array EXIR, 120m IR , Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD(Coaxitron), 120dB WDR , IP66, Lentila varifocala zoom motorizat 5-50 mm ; DC 12V/AC 24V max. 20W	709
DS-2CE16F1T-IT		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 20m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP66, Lentila 2.8 mm; DC 12V/max. 5W	155
DS-2CE16F1T-IT3		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 40m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP66, Lentila 2.8 mm; DC 12V/max. 5W	155
DS-2CE16F1T-IT5		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 80m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP66, Lentila 3.6 mm; DC 12V/max. 5W	197
DS-2CE16F7T-IT		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 20m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron), 120dB WDR , IP66, Lentila 2.8 mm; DC 12V/max. 5W	207
DS-2CE16F7T-IT3		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 40m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron), 120dB WDR , IP66, Lentila 2.8 mm; DC 12V/max. 5W Disponibila si cu lentila de 3,6 mm	240
DS-2CE16F7T-IT3Z		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 40m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron), 120dB WDR , IP66, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 6W	425
DS-2CE16F7T-IT5		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 80m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron), 120dB WDR , IP66, Lentila 3.6 mm; DC 12V/max. 5W	254
DS-2CE16H5T-IT		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 20m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2.8 mm; DC 12V/max. 5W	209
DS-2CE16H5T-IT3		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2,8 mm; DC 12V/max. 5W Disponibila si cu lentila de 3,6 mm	226
DS-2CE16H5T-IT3Z		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 5W	396
DS-2CE16H5T-IT5		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 80m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 3.6 mm; DC 12V/max. 5W Disponibila si cu lentila de 6 mm	263
DS-2CE38D8T-PIR		2MP	TURBO HD CUBE, 2 Megapixel high-performance CMOS, ICR, 0.005 Lux/F1.2 AGC ON, Meniu OSD(Coaxitron), 120dB WDR , Lentila 2.8 mm; Microfon incorporat; lesire audio 1 RCA; PIR incorporat 110°/11m ; DC 12V/max. 5W; Dimensiuni: 104 mm × 66 mm × 41.04 mm; Greutate:210g	163
DS-2CE55C2P-VFIR3		PAL	720 TVL ; 1/3" PICADIS; Senzor 1.3 MP ; Rezolutie: 1280x960; True Day/Night; Lentila 2.8~12mm ; IR Cut filter; Smart IR, High Dynamic Range; IR 30~40m; Antivandal; IP66; Temperatura Functionare -40°C~+50°C; DC 12V/max. 5W	200
DS-2CE56C0T-VFIR3F		1MP	4in1, 1 Megapixel CMOS, 1 LED Array EXIR, 40m IR, Dome ABS, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, IP66, Interval mare al temperaturii de functionare (-40°~60°), Lentila 2,8-12 mm; DC 12V/max. 4W lesire TVI/AHD/CVI/CVBS selectabila	183

DS-2CE56C2T-VFIR3		1MP	TURBO HD, 1 Megapixel , 1/3" Progressive Scan CMOS, 36 LEDuri IR, 40m IR, Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, IP66, Interval mare al temperaturii de functionare (-40°~60°), Lentila 2.8-12 mm ; DC 12V/max. 4,5W	169
DS-2CE56D0T-IRMF		2MP	4in1, 2 Megapixel High Performance CMOS, 24 LEDuri IR, 20m IR, Dome metalic, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, Digital WDR, IP66, Lentila 2.8mm ; DC 12V/max. 4W Iesire TVI/AHD/CVI/CVBS selectabila	104
DS-2CE56D0T-IRPF		2MP	4in1, 2 Megapixel High Performance CMOS, 24 LEDuri IR, 20m IR, Dome carcasa ABS, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, Digital WDR, Lentila 2,8mm ; DC 12V/max. 4W Iesire TVI/AHD/CVI/CVBS selectabila	92
DS-2CE56D0T-IT3F		2MP	4in1, 2 Megapixel High Performance CMOS, LED Array EXIR, 40m IR, Dome ABS, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Digital WDR, IP66, Lentila 2,8 / 3,6 mm ; DC 12V/max. 3W Iesire TVI/AHD/CVI/CVBS selectabila	138
DS-2CE56D1T-VFIRF		2MP	4in1, 2 Megapixel High Performance CMOS, IR 40m, Dome ABS, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Digital WDR, IP66, Lentila varifocala 2.8-12mm ; DC 12V/max. 3W Iesire TVI/AHD/CVI/CVBS selectabila	183
DS-2CE56D8T-IT3		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m IR, Dome ABS, 0.005 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP66, Lentila 2.8 mm ; DC 12V/max. 5W Disponibila si cu lentila de 3,6 mm	169
DS2CE56D8T-IT3Z		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m IR, Dome metalic, ICR, 0.005 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP66, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 6W	283
DS-2CE56D8T-ITM		2MP	TURBO HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 20m IR, Dome metalic, ICR, 0.005 Lux/F2.0 AGC ON , Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila 2.8 mm ; DC 12V/max. 4W	146
DS-2CE56F1T-ITM		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 20m IR, Dome metalic, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , IP66, Lentila 2.8 mm ; DC 12V/max. 5W	141
DS2CE56F7T-IT3Z		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 40m IR, Dome metalic, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD (Coaxitron) , 120dB WDR , IP66, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 6W	425
DS-2CE56F7T-ITM		3MP	TURBO HD, 3 Megapixel high-performance CMOS, LED Array EXIR, 20m IR, Dome metalic, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP66, Lentila 2.8 mm ; DC 12V/max. 5W	212
DS-2CE56H5T-IT3		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Dome antivandal, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 3.6 mm ; DC 12V/max. 5W	240
DS-2CE56H5T-IT3Z		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Dome antivandal, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/max. 5W	410
DS-2CE56H5T-ITM		5MP	TURBO HD, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 20m IR, Dome antivandal, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2.8 mm ; DC 12V/max. 5W	212
DS-2CS54D7T-PH		2MP	TURBO HD COVERT, 2 Megapixel high-performance CMOS, ICR, 0.01 Lux/F1.2 AGC ON , Meniu OSD(Coaxitron) , 120dB WDR , Lentila 2.8 mm ; DC 12V/max. 1.5W; Dimensiuni: 32.4 mm x 32.4 mm x 22.0 mm; Greutate:200g	254
DS-7104HQHI-F1/N		2MP	DVR TURBO HD 4 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.264+ ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 1080P @10 fps/ch, 720P / VGA / WD1 / 4CIF / CIF @25fps/ch sau Mod 1080P Lite 1080P Lite / 1280x720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 1 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 2 USB2.0; Alimentare: DC 12V/8W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 200(W)x200(D)x45(H)mm; Greutate: 0.8Kg;Protocol Hikvision-C(Coaxitron) Compatibil standard HD-TVI/AHD/CVI	212

DS-7204HQHI-K1		3MP	DVR TURBO HD 4 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 1 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 1 camera IP 4Mpx	268
DS-7204HUHI-K1		5MP	DVR TURBO HD 5Mpx 4 Ch IN Video, 4 IN/1 OUT Ch Audio; 4 IN/1 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 1 HDD Port SATA/8TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 1.5Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 2 camere IP 6Mpx	439
DS-7204HUHI-K2		5MP	DVR TURBO HD 5Mpx 4 Ch IN Video, 4 IN/1 OUT Ch Audio; 4 IN/1 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 2 HDD Port SATA/8TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x240(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 2 camere IP 6Mpx	515
DS-7208HGHI-F1/N		1MP	DVR TURBO HD 8 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch ; 1 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 2 USB2.0; Alimentare: DC 12V/12W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 260(W)x222(D)x45(H)mm; Greutate: 1Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD max.720p	226
DS-7208HQHI-K1		2MP	DVR TURBO HD 8 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH2), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 1 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/20W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 2 camere IP 4Mpx	481
DS-7208HQHI-K2		3MP	DVR TURBO HD 8 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K , VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH2), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 2 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x320(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 2 camere IP 4Mpx	524

DS-7208HUHI-K1		5MP	DVR TURBO HD 5Mpx 8 Ch IN Video, 4 IN/1 OUT Ch Audio; 8 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K (3840 × 2160), VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps, 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 1 HDD Port SATA/8TB; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 USB2.0; 1 USB3.0; Alimentare: DC 12V/20W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 4 camere IP 6Mpx	690
DS-7208HUHI-K2		5MP	DVR TURBO HD 5Mpx 8 Ch IN Video, 4 IN/1 OUT Ch Audio; 8 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K (3840 × 2160), VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps, 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 2 HDD Port SATA/8TB; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 USB2.0; 1 USB3.0; Alimentare: DC 12V/20W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x240(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 4 camere IP 6Mpx	822
DS-7216HQHI-K1		3MP	DVR TURBO HD 16 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K, VGA maxim: 1920x1080, CVBS 704x576; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH4), 1080P @15fps, 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite; 1 HDD Port SATA/6TB; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron) Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 2 camere IP 4Mpx	663
DS-7216HQHI-K2		3MP	DVR TURBO HD 16 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K, VGA maxim: 1920x1080, CVBS 704x576; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH4), 1080P @15fps, 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 2 HDD Port SATA/6TB; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x320(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 2 camere IP 4Mpx	694
DS-7216HQHI-K2/16A		3MP	DVR TURBO HD 16 Ch IN Video, 16 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K, VGA maxim: 1920x1080, CVBS 704x576; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH4), 1080P @15fps, 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 2 HDD Port SATA/6TB; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x320(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch; Suporta 2 camere IP 4Mpx	1035
DS-7216HUHI-K2		5MP	DVR TURBO HD 5Mpx 16 Ch IN Video, 4 IN/1 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K (3840 × 2160), VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps, 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 2 HDD Port SATA/8TB; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 USB2.0; 1 USB3.0; Alimentare: DC 12V/20W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x240(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 8 camere IP 6Mpx	1419

DS-7216HUHI-K2/16A		5MP	DVR TURBO HD 5Mpx 16 Ch IN Video, 16 IN/1 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K (3840 × 2160) , VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 2 HDD Port SATA/8TB ; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 USB2.0; 1 USB3.0; Alimentare: DC 12V/20W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x240(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele; Suporta 8 camere IP 6Mpx	1774
DS-7316HQHI-K4		3MP	DVR TURBO HD 16 Ch IN Video, 4 IN/2 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI2 maxim 4K (3840 × 2160) ,HDMI1/VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 3Mpx (doar CH1-CH4) / 1080P@15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 4 HDD Port SATA/8TB; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet;1 RS-232; 1 RS-485; Keyboard; 2 USB2.0; 1 USB3.0; Alimentare: AC 220V/45W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm;Protocol Hikvision-C(Coaxitron) Compatibil standard HD-TVI/AHD/CVI, Suporta pina la 18 camere IP 4Mpx	2043
DS-7316HUHI-K4		5MP	DVR TURBO HD 16 Ch IN Video, 4 IN/2 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI2 maxim 4K (3840 × 2160) ,HDMI1/VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5 MP@12fps, 4 MP@15fps, 3 MP@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 4 HDD Port SATA/8TB; RAID 0, RAID 1, RAID 5, RAID 6, RAID 10 ; Dual-stream; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-232; 1 RS-485; Keyboard; 2 USB2.0; 1 USB3.0; Alimentare: AC 220V/74W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm;Protocol Hikvision-C(Coaxitron) Compatibil standard HD-TVI/AHD/CVI, Suporta pina la 18 camere IP 8Mpx	2682
DS-7332HQHI-K4		4MP	DVR TURBO HD 32 Ch IN Video, 4 IN/2 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI2 maxim 4K (3840 × 2160) ,HDMI1/VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 4Mpx / 3Mpx (doar CH1-CH4) / 1080P@15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 4 HDD Port SATA/8TB; Dual-stream; 1 RJ45 10M/100M/1000M Ethernet;1 RS-232; 1 RS-485; Keyboard; 2 USB2.0; 1 USB3.0; Alimentare: AC 220V/45W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm;Protocol Hikvision-C(Coaxitron) Compatibil standard HD-TVI/AHD/CVI, Suporta pina la 40 camere IP 6Mpx	3080
DS-7332HUHI-K4		5MP	DVR TURBO HD 32 Ch IN Video, 4 IN/2 OUT Ch Audio; 16 IN/4 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI2 maxim 4K (3840 × 2160) ,HDMI1/VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5 MP@12fps, 4 MP@15fps, 3 MP@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 4 HDD Port SATA/8TB; RAID 0, RAID 1, RAID 5, RAID 6, RAID 10 ; Dual-stream; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-232; 1 RS-485; Keyboard; 2 USB2.0; 1 USB3.0; Alimentare: AC 220V/74W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 440(W)x390(D)x70(H)mm;Protocol Hikvision-C(Coaxitron) Compatibil standard HD-TVI/AHD/CVI, Suporta pina la 40 camere IP 8Mpx	4344
DS-9116HWI-ST			DVR 16 Ch IN/16 OUT (loop) Video , 4 Ch OUT Video Spot, 16 IN/2 OUT Ch Audio, 16 IN/4 OUT Ch Alarma; Compresie Video: H.264; Compresie Audio: OggVorbis; Iesiri Video: VGA, MAIN, HDMI; Rezolutie maxima: 1920x1080P; Inregistrare/Ch: VGA / WD1 / 4CIF / CIF@25fps/ch ; Redare Sincrona: 16 Ch; 8 HDD Port SATA/4TB ; 2 RJ45 10M/100M/1000M Ethernet; 1 e-SATA; 1 RS-232; 3 RS-485; 2 USB2.0; Alimentare: 100~240VAC/6.3A; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 470(D)x445(W)x90(H)mm; 19" standard 2U pentru montare rack; Greutate: 8Kg	2839

CCTV ANALOGIC/HD-TVI PoC

PRODUS	IMAGINE	REZOLUTIE	DESCRIERE PRODUS	#VALUE!
DS-2CE16D0T-IRE		2MP	TURBO HD PoC, 2 Megapixel High Performance CMOS, 24 LEDuri IR, 20m IR, Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, IP66, Lentila 2.8 mm; DC 12V/PoC.af max. 4W Compatibila si cu DVRurile standard	115
DS-2CE16D0T-IT3E		2MP	TURBO HD PoC, 2 Megapixel High Performance CMOS, LED Array EXIR, 40m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, IP66, Lentila 2.8 mm; DC 12V/PoC.af max. 4W Compatibila si cu DVRurile standard	141
DS-2CE16D0T-IT5E		2MP	TURBO HD PoC, 2 Megapixel High Performance CMOS, LED Array EXIR, 80m IR, Bullet, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, IP66, Lentila 3.6mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	152
DS-2CE16D8T-IT3E		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila 2.8mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile PoC	183
DS-2CE16D8T-IT3ZE		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/PoC.af max. 6W Compatibila si cu DVRurile standard	297
DS-2CE16D8T-IT5E		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 80m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila 3.6mm; DC 12V/PoC.af max. 6W Disponibila si cu lentila de 6 mm Compatibila si cu DVRurile standard	212
DS-2CE16D8T-ITE		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 20m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP67, Lentila 2.8 mm; DC 12V/PoC.af max. 4W Compatibila si cu DVRurile standard	163
DS-2CE16H5T-IT3E		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2,8 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	250
DS-2CE16H5T-IT3ZE		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 40m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	425
DS-2CE16H5T-IT5E		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 80m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 3.6 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	283
DS-2CE16H5T-ITE		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps , LED Array EXIR, 20m IR, Bullet, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2.8 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	226
DS-2CE56D0T-IT3E		2MP	TURBO HD PoC, 2 Megapixel High Performance CMOS, LED Array EXIR, 40m IR, Dome ABS, ICR, 0.01 Lux/F1.2, Smart IR, 3D DNR, Digital WDR, IP66, Lentila 2.8 mm; DC 12V/PoC.af max. 3W Compatibila si cu DVRurile standard	152
DS-2CE56D8T-IT3E		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m IR, Dome ABS, 0.005 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP66, Lentila 2.8 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	183
DS2CE56D8T-IT3ZE		2MP	TURBO HD PoC LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m IR, Dome metalic, ICR, 0.005 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD(Coaxitron) , 120dB WDR , IP66, Lentila varifocala zoom motorizat 2.8-12 mm ; DC 12V/PoC.af max. 6W Compatibila si cu DVRurile standard	311

DS-2CE56H5T-IT3E		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps, LED Array EXIR, 40m IR, Dome antivandal, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila 2.8 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	254
DS-2CE56H5T-IT3ZE		5MP	TURBO HD PoC, 5 Megapixel high-performance CMOS, 2560 x 1944 @ 20fps, LED Array EXIR, 40m IR, Dome antivandal, ICR, 0.008 Lux/F1.2 , Smart IR, 3D DNR, Meniu OSD (Coaxitron) , IP67, Lentila varifocala zoom motorizat 2.8-12 mm; DC 12V/PoC.af max. 5W Compatibila si cu DVRurile standard	439
DS-7204HQHI-K1/P		3MP	DVR TURBO HD PoC 4 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 1 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 48V/40W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch, Suporta 1 camere IP 4Mpx	396
DS-7204HUHI-K1/P		5MP	DVR TURBO HD PoC 5Mpx 4 Ch IN Video, 4 IN/1 OUT Ch Audio; 4 IN/1 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 1 HDD Port SATA/8TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 48V/40W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x242(D)x45(H)mm; Greutate: 1.5Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele, Suporta 2 camere IP 6Mpx	564
DS-7208HQHI-K2/P		3MP	DVR TURBO HD PoC 8 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K , VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH2), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 2 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 48V/60W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x320(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch, Suporta 2 camere IP 4Mpx	687
DS-7208HUHI-K2/P		5MP	DVR TURBO HD PoC 5Mpx 8 Ch IN Video, 4 IN/1 OUT Ch Audio; 4 IN/1 OUT Alarma; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI, VGA maxim: 1920x1080; Rezolutie Inregistrare/Ch: 5MP@12fps/4MP@15fps/3Mpx@18fps , 1080P / 720P / VGA / WD1 / 4CIF / CIF@25fps/ch; 2 HDD Port SATA/8TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 48V/40W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x240(D)x48(H)mm; Greutate: 1.5Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru toate canalele, Suporta 4 camere IP 6Mpx	1064
DS-7216HQHI-K2/P		3MP	DVR TURBO HD PoC 16 Ch IN Video, 1 IN/1 OUT Ch Audio; Compresie Video: H.265+/H.265/H.264+/H.264 ; Compresie Audio: G.711u; Iesiri Video: HDMI maxim 4K , VGA maxim: 1920x1080, CVBS 704x576 ; Rezolutie Inregistrare/Ch: 3MP@15fps(doar CH1-CH4), 1080P @15fps , 720P / VGA / WD1 / 4CIF / CIF@25fps/ch sau Mod 1080P Lite 1080P Lite @25fps/ch; 2 HDD Port SATA/6TB ; Dual-stream; 1 RJ45 10M/100M Ethernet; 1 RS-485; 2 USB2.0; Alimentare: DC 12V/15W; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 380(W)x320(D)x48(H)mm; Greutate: 2Kg; Protocol Hikvision-C(Coaxitron); Compatibil standard AHD/CVI max.1080p Functii smart (line crossing / intrusion detection) pentru max. 2 ch, Suporta 2 camere IP 4Mpx	1220

CCTV IP

PRODUS	IMAGINE	REZOLUTIE	DESCRIERE PRODUS	#VALUE!
NOU				#VALUE!
DS-2CD2045FWD-I		4MP	4 Megapixel , Mini Bullet Camera cu ExIR 30m; 1/2,5" Progressive scan CMOS; 0.008 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2688x1520 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ70 × 155.03 mm; Greutate: 410g;Standard: ONVIF, PSIA, CGI	425
DS-2CD2055FWD-I		5MP	5 Megapixel , Mini Bullet Camera cu ExIR 30m; 1/2,9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2,8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ70 × 155.03 mm; Greutate: 410g;Standard: ONVIF, PSIA, CGI	467
DS-2CD2085FWD-I		8MP	8 Megapixel , Mini Bullet Camera cu ExIR 30m; 1/2,5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2,8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080); Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ70 × 155.03 mm; Greutate: 410g;Standard: ONVIF, PSIA, CGI Disponibila si cu lentila de 4mm	623
DS-2CD2142FWD-I		4MP	4 Megapixel , Dome Camera cu IR 20m; 1/3" Progressive Scan CMOS; Rezolutie: 4MP; Day/Night, WDR120db , BLC, 3D DNR; ROI; 0.01Lux/F:1.2, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 2.8mm ; Distanta Iluminare: max. 30m; Frame: 20fps(2688x1520), 25fps(1920x1080), 25fps(1280x720); Detectie miscare, Tamper; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC, PoE; Standard: IP67; Protectie impact: IEC600068-2-75Eh, 50J, EN50102, IK10; Dimensiuni: Ø 111 x 82mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI	396
DS-2CD2142FWD-IWS		4MP	Camera dome antivandal IP cu IR; 1/3" Progressive Scan CMOS; Rezolutie: 4MP; Day/Night, WDR120db, BLC, 3D DNR; ROI; 0.01Lux/F:1.2, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 2.8mm; Distanta Iluminare: max. 30m; Frame: 20fps(2688x1520), 25fps(1920x1080), 25fps(1280x720); Detectie miscare, Tamper; Posibilitate stocare pe card SD/SDHC, NAS;Audio I/O, Alarm I/O; 1 RJ45 10M/100M Ethernet; WI-FI 802.11b/g/n; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC, PoE; Standard: IP67; Protectie impact: IEC600068-2-75Eh, 50J, EN50102, IK10; Dimensiuni: Ø 111 x 82mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI	496
NOU				
DS-2CD2145FWD-I		4MP	4 Megapixel , Dome Camera cu ExIR 20m; 1/2,5" Progressive scan CMOS; 0.008 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2688x1520 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Protectie impact: IEC600068-2-75Eh, 50J, EN50102, IK10; Dimensiuni: Ø 111 x 82mm; Greutate: 500g;Standard: ONVIF, PSIA, CGI	439
DS-2CD2155FWD-I		5MP	5 Megapixel , Dome Camera cu ExIR 20m; 1/2,9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2,8mm ; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni:Φ 111 × 82.4 mm; Greutate: 500g;Standard: ONVIF, PSIA, CGI	467

DS-2CD2185FWD-I		8MP	8 Megapixel , Dome Camera cu ExIR 20m; 1/2,5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2,8mm ; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080); Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ 111 × 82.4 mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI Disponibil si cu lentila de 4 mm	609
DS-2CD2325FWD-I		2MP	2 Megapixel , Turret Camera cu ExIR 20m; 1/2,8" Progressive scan CMOS; 0.005 Lux/F1.2; Lentila fixa: 2,8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; NAS; Posibilitate stocare pe card SD/SDHC; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ 111 × 82.4 mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI Disponibil si cu lentila de 4 mm	410
DS-2CD2342WD-I		4MP	4 Megapixel , Turret Camera cu ExIR 20m; 1/3" Progressive Scan CMOS; Rezolutie: 4MP; Day/Night, WDR120db , BLC, 3D DNR; ROI; 0.01Lux/F:1.2, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 2,8mm ; Distanta Iluminare: max. 30m; Frame: 20fps(2688x1520), 25fps(1920x1080), 25fps(1280x720); Detectie miscare, Tamper; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC, PoE; Standard: IP67; Protectie impact: IEC600068-2-75Eh, 50J, EN50102, IK10; Dimensiuni: Ø 127 x 97.5mm; Greutate: 650g; Standard: ONVIF, PSIA, CGI	396
NOU DS-2CD2345FWD-I		4MP	4 Megapixel , Turret Camera cu ExIR 20m; 1/2,5" Progressive scan CMOS; 0.008 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2688x1520 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Protectie impact: IEC600068-2-75Eh, 50J, EN50102, IK10; Dimensiuni: Ø 111 x 82mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI	439
DS-2CD2355FWD-I		5MP	5 Megapixel , Turret Camera cu ExIR 20m; 1/2,9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; NAS; Posibilitate stocare pe card SD/SDHC; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ 111 × 82.4 mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI Disponibil si cu lentila de 4 mm	453
DS-2CD2385FWD-I		8MP	8 Megapixel , Turret Camera cu ExIR 20m; 1/2,5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080); Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: Φ 111 × 82.4 mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI Disponibil si cu lentila de 4 mm	595
DS-2CD2442FWD-IW		4MP	IP Mini Cube Camera, 4 Megapixel, IR 10m; 1/3" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120db , BLC, 3D DNR; ROI; Compresie: H264; Rezolutie max.: 2688x1520 / 20fps, 1920x1080 / 25fps ; Dual stream; PIR: 10m, unghi detectie 80° ; 1 RJ45 10M/100M Ethernet; WI-FI 802.11b/g/n; Posibilitate stocare pe card SD/SDHC; Alarma I/O; Microfon si difuzor incorporat ; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC/5W max., PoE; Dimensiuni: 102.8x65.2x32.6mm; Greutate: 128g; Compatibila cu standardele: PSIA, ONVIF, CGI	410

NOU		5MP	IP Mini Cube Camera, 5 Megapixel, IR 10m; 1/2.8" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2.8mm; Day&Night, WDR 120db , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264 ; Rezolutie max.: 2944 × 1656 / 20fps, 2560 × 1440, 1920x1080 / 25fps ; Dual stream; PIR: 10m, unghi detectie 80° ; 1 RJ45 10M/100M Ethernet; WI-FI 802.11b/g/n; Posibilitate stocare pe card SD/SDHC; Alarma I/O; Microfon si difuzor incorporat ; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC/5W max., PoE; Dimensiuni: 66x70.6x139.1mm; Greutate: 400g; Compatibila cu standardele: PSIA, ONVIF, CGI	496
DS2CD2625FWD-IZS		2MP	2 Megapixel, Bullet Camera cu ExIR 50m ; 1/2.8" Progressive scan CMOS; 0.005 Lux/F1.2 ; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /17.5W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	723
DS2CD2655FWD-IZS		5MP	5 Megapixel, Bullet Camera cu ExIR 50m ; 1/2.9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /17.5W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	879
DS2CD2685FWD-IZS		8MP	8 Megapixel, Bullet Camera cu ExIR 50m ; 1/2.5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 3840x2160 / 20fps, 2944x1656 / 25fps, 2560x1440 / 25fps, 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /19W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	1049
DS2CD2725FWD-IZS		2MP	2 Megapixel, Dome Camera cu ExIR 50m ; 1/2.8" Progressive scan CMOS; 0.005 Lux/F1.2 ; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /17.5W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	709
DS2CD2742FWD-IZS		4MP	4 Megapixel, Camera dome antivandal IP cu IR ; 1/3" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night, WDR 120db, BLC, 3D DNR; ROI; Compresie: H264; Rezolutie max.: 2688x1520 / 20fps, 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /6.5W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA	808
DS2CD2752F-IZS		5MP	5 Megapixel, Camera dome antivandal IP cu IR ; 1/3" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night, DWDR, BLC, 3D DNR; ROI; Compresie: H264; Rezolutie max.: 2560 x 1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /6.5W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA	886
DS2CD2755FWD-IZS		5MP	5 Megapixel, Dome Camera cu ExIR 50m ; 1/2.9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /11.5W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	907

DS2CD2785FWD-IZS		8MP	8 Megapixel, Dome Camera cu ExIR 50m; 1/2,5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila zoom motorizat:2.8-12mm; Day&Night,WDR 120db, BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 3840×2160 / 20fps, 2944×1656 / 25fps, 2560×1440 / 25fps, 1920×1080 / 25fps; Dual stream; Audio I/O, Alarm I/O; Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; BNC; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /13W cu ICR; Standard: IP67, IK10; Compatibila cu standardul ONVIF, PSIA	993
DS-2CD2F42FWD-IWS		4MP	IP Mini IR PT Camera, 4Mpx; 1/3" Progressive Scan CMOS; Rezolutie: 4MP; Day/Night, WDR120db, BLC, 3D DNR; ROI; 0.01Lux/F:1.2, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 4mm; Distanța Iluminare: max. 10m; Frame: 20fps(2688x1520), 25fps(1920x1080), 25fps(1280x720); Detectie miscare; WI-FI 802.11b/g/n; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Audio I/O, Alarm I/O ; Temperatura de operare: -10°C~+40°C; Alimentare: 12VDC, PoE; Dimensiuni: Ø 119.93 x 87mm; Greutate: 500g; Standard: ONVIF, PSIA, CGI	538
DS-2CD2T25FWD-IS		2MP	2 Megapixel , Bullet Camera cu IR 50m (2xEXIR); 1/2,8" Progressive scan CMOS; 0.005 Lux/F1.2; Lentila fixa: 2,8mm ; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; ONVIF, PSIA, CGI; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C;IP67 Disponibila si cu lentila de 4mm si 6mm	425
DS-2CD2T45FWD-IS		4MP	4 Megapixel , Bullet Camera cu ExIR 50m (2xEXIR); 1/2.5" Progressive scan CMOS; 0.008 Lux/F1.2; Lentila fixa: 2.8mm ; Day&Night, WDR120db , BLC, 3D DNR; ROI; Compresie: H265/H264 ; Rezolutie max.: 2688x1520, 2304x1296, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC;NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: 299.71 × 86.48 × 85.11 mm; Greutate: 1200g;Standard: ONVIF, PSIA, CGI	481
DS-2CD2T45FWD-I8		4MP	4 Megapixel , Bullet Camera cu ExIR 80m (4xEXIR); 1/2.5" Progressive scan CMOS; 0.008 Lux/F1.2; Lentila fixa: 4 / 6 mm ; Day&Night, WDR120db , BLC, 3D DNR; ROI; Compresie: H265/H264 ; Rezolutie max.: 2688x1520, 2304x1296, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet; Posibilitate stocare pe card SD/SDHC;NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Dimensiuni: 299.71 × 86.48 × 85.11 mm; Greutate: 1200g;Standard: ONVIF, PSIA, CGI	496
DS-2CD2T55FWD-I8		5MP	5 Megapixel , Bullet Camera cu ExIR 80m (4xEXIR); 1/2,9" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa 4mm ; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 2560x1920 / 20fps, 2048x1536 / 25fps, 1920x1080 / 25fps; Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67;Standard: ONVIF, PSIA, CGI Disponibila si cu lentila de 6/8/12 mm	524
DS-2CD2T85FWD-I8		8MP	8 Megapixel , Bullet Camera cu ExIR 80m; 1/2,5" Progressive scan CMOS; 0.01 Lux/F1.2; Lentila fixa: 2,8mm ; Day&Night, WDR 120dB , BLC, 3D DNR; ROI; Compresie: H.265+/H.265/H.264+/H.264/MJPEG ; Rezolutie max.: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080); Dual stream; Network: 10M/100M Ethernet;Posibilitate stocare pe card SD/SDHC; NAS; Detectie miscare; Alimentare: DC 12V, PoE; Temperatura de operare: -30°C ~ +60°C; IP67; Standard: ONVIF, PSIA, CGI Disponibila si cu lentila de 4/6/8 mm	737
DS-2CD4525FWD-IZ		2MP	Camera Dome Exterior IP LightFighter ; 1/2.8" Progressive Scan CMOS; Rezolutie: 2MP; Day/Night; 0.005Lux/F:1.2; Lentila Zoom Motorizat 2.8-12mm; Compresie video: H.264; 140db WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection; Frame: 50fps (1920 × 1080)/(1280 × 960)/(1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /12W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI	1135

DS-2CD4526FWD-IZ		2MP	Camera Dome Exterior IP DarkFighter ; 1/2.8" Progressive Scan CMOS; Rezolutie: 2MP; Day/Night; 0.002Lux/F:1.2; Lentila Zoom Motorizat 2.8-12mm; Compresie video: H.264; 120db WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection; Frame: 50fps(1920 × 1080, 1280 × 960, 1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /12W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI	1376
DS-2CD4565F-IZH		6MP	Camera Dome Exterior IP LightFighter ; 1/2.8" Progressive Scan CMOS; Rezolutie: 6MP; Day/Night; 0.01Lux/F:1.2; Lentila Zoom Motorizat 2.8-12mm; Compresie video: H.264; 120db WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection; Frame: 24fps (3072 × 2048), 25fps (3072 × 1728, 2560 × 2048, 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /17W cu SmartHeater; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI	3662
DS2CD4A26FWD-IZS/P		2MP	Camera Bullet Exterior IP DarkFighter ; 1/2.8" Progressive Scan CMOS; Rezolutie: 2MP; Day/Night; 0.002Lux/F:1.2; Lentila Zoom Motorizat 2,8-12mm; IR 50m ; Compresie video: H.264; 120dB WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection, audio exception detection; Frame: 50fps (1920 × 1080)/(1280 × 960)/(1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Audio: 1IN/1OUT; Alarma: 1IN/1OUT; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /12W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI Rata recunoastere LPR >96% pentru viteze <70km/h, viteza max. 120km/h	2484
DS2CD4A26FWD-IZS/P		2MP	Camera Bullet Exterior IP DarkFighter ; 1/2.8" Progressive Scan CMOS; Rezolutie: 2MP; Day/Night; 0.002Lux/F:1.2; Lentila Zoom Motorizat 8-32mm; IR 100m ; Compresie video: H.264; 120dB WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection, audio exception detection; Frame: 50fps (1920 × 1080)/(1280 × 960)/(1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Audio: 1IN/1OUT; Alarma: 1IN/1OUT; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /12W cu ICR; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI Rata recunoastere LPR >96% pentru viteze <70km/h, viteza max. 120km/h	2725
DS-2CD4A85F-IZHS		8MP	Camera Bullet Exterior IP LightFighter ; 1/1.7" Progressive Scan CMOS; Rezolutie: 8MP ; Day/Night; 0.01Lux/F:1.2; Lentila Zoom Motorizat 2.8-12mm; Compresie video: H.264; 120db WDR; ROI; EIS; DeFog; Triple Streams; Smart Focus; Line crossing detection, intrusion detection, scene change detection ; Frame: 22fps (4096 × 2160), 25fps (3840 × 2160, 1920 × 1080, 1280 × 720); Detectie miscare; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Audio: 1IN/1OUT; Alarma: 1IN/1OUT; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; PoE /12W; Standard: IP67; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI	3478
DS-2CD6362F-IVS		6MP	IP FishEye Camera, 6MPx , IR 15m; 1/1.8" Progressive Scan CMOS; 0.3 Lux/F:1.2, DWDR; Day&Night;3D DNR; Lentila 1.27 mm unghi vizualizare 360°; Compresie video: H.264/ MJPEG, Compresie audio: G.711/G.726/MP2L2; Microfon si difuzor integrate; Frame: High-frame Mode: 1 x fisheye (3072 x 2048, 25fps) or (2048 x 2048, 30fps) or 4 x PTZ at (1024 x 768, 30fps) / Multi-channel Mode: 1 x fisheye (1280 x 1280, 15fps) and 1 x panoramic (2048 x 1536, 15fps) and 3 x PTZ(1024 x 768, 15fps); Stream-uri 1 sau 4/5; 1 suport micro SD card 128GB max.; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC/11W max., PoE; IP67;IK10 vandal proof; Dimensiuni: 164x152.8x43.8mm; Greutate: 1400g; Compatibila cu standardele: PSIA, ONVIF, CGI. Functia de "HeatMap" se poate realiza folosind card SD, NVR, IVMS-5200	2299

DS-2CD63C2F-IVS		12MP	IP FishEye Camera, 12MPx, IR 15m; 1/1.8" Progressive Scan CMOS; 0.3 Lux/F:1.2, DWDR; Day&Night;3D DNR; Lentila 1.98 mm unghi vizualizare 360°; Compresie video: H.264/ MJPEG, Compresie audio: G.711/G.726/MP2L2; Microfon si difuzor integrate; Frame: Mode1: 1×Fisheye(2560×2560, 2048×2048, 1280×1280, 10fps) + 1×Fisheye(720×720, 10fps) +3×PTZ(1600×1200, 10fps) / Mode2:1×Panorama(3072×2304, 3072×1152, 12.5fps) + 1×Panorama(704×576, 12fps) / Mode3: 4×PTZ(1600×1200,12.5fps) / Mode4: 1×Fisheye(4000×3072, 20fps,3072×3072, 2560×2560, 25fps)+1×fisheye(720×720, 704×576, 12.5fps); Stream-uri 1 sau 4/5; 1 suport micro SD card 128GB max.; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC/11W max., PoE; IP67;IK10 vandal proof; Dimensiuni: 164x152.8x43.8mm; Greutate: 1400g; Compatibila cu standardele: PSIA, ONVIF, CGI Funcția de "HeatMap" se poate realiza folosind card SD, NVR, IVMS-5200	3066
DS-2CD6424FWD-10		2MP	Covert network camera; 1/2,7" Progressive Scan CMOS; Rezolutie: 2MP; Day/Night, WDR 120db, BLC, 3D DNR; ROI; 0.028Lux/F:2.0, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 3,7 mm; Audio 1 In / 1 Out, Alarm 1 In / 1 Out; Frame:25fps (1920×1080), 25fps(1280x960), 25fps(1280x720); Detectie miscare, Tamper; Posibilitate stocare pe card SD/SDHC,NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; Cablu 8m; Standard: ONVIF, PSIA, CGI	1191
DS-2DE2204IW-DE3/W		2MP	IP Mini IR PTZ Camera, 2Mpx; 1/2.8" Progressive Scan CMOS; Rezolutie: 1920x1080@25fps; Day/Night, BLC, 3D DNR; ROI; Color: 0.05 Lux @(F2.0, AGC ON) B/W: 0.005 Lux @(F2.0, AGC ON); Compresie video: H.265+/H.265/H.264+/H.264, MJPEG; Lentila zoom motorizat: 4x; Distanța Iluminare: max. 20m; Detectie miscare; WI-FI 802.11b/g/n; Posibilitate stocare pe card SD/SDHC, NAS; 1 RJ45 10M/100M Ethernet; Audio I/O, Alarm I/O; Temperatura de operare: -10°C~+50°C; Alimentare: 12VDC, PoE; Dimensiuni: Ø 125 x 136.7mm; Greutate: 650g; Standard: ONVIF, PSIA, CGI	1078
DS-2DE4215IW-DE		2MP	Speed Dome IP Exterior; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.05 Lux/F:1.6; B&W: 0.01 Lux/F:1.6; ICR; Zoom optic: 15x; Zoom digital: 16x; Lentila: 5~75mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 160°/s; Tilt Manual Speed: 0.1° ~ 120°/s,Tilt Preset Speed: 120°/s; Distanța IR: 100m, ajustabila de zoom; IP67;Micro SD Slot; Ethernet 10/100; 12 VDC, PoE, Max.18W; Dimensiuni:Φ164.5×295 mm; Greutate:2kg SURSA 12VDC si SUPORT DS-1602ZJ INCLUSE	1206
DS-2DE4220-AE3		2MP	Speed Dome IP Interior; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.05 Lux/F:1.6; B&W: 0.01 Lux/F:1.6; ICR; Zoom optic: 20x; Zoom digital: 16x; Lentila: 4.7~94mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 160°/s; Tilt Manual Speed: 0.1° ~ 120°/s,Tilt Preset Speed: 120°/s; Audio 1 IN/ 1 OUT;Alarma 1 IN/ 1 OUT;Micro SD Slot; Ethernet 10/100; 24VAC/PoE(802.3af), Max 12W; Dimensiuni:Φ165×179.5mm; Greutate:2kg SURSA 24VAC INCLUSA	1541
DS-2DE4225IW-DE		2MP	Speed Dome IP Exterior; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 20x; Zoom digital: 16x; Lentila: 4.8~120mm; Pan Manual Speed: 0.1° ~ 80°/s, Pan Preset Speed: 80°/s; Tilt Manual Speed: 0.1° ~ 80°/s,Tilt Preset Speed: 80°/s; Audio 1 IN/ 1 OUT;Alarma 1 IN/ 1 OUT; Distanța IR: 100m, ajustabila de zoom; IP67;Micro SD Slot; Ethernet 10/100; 12 VDC, PoE, Max.20W; Dimensiuni:Φ164.5×295 mm; Greutate:2kg SURSA 12VDC si SUPORT DS-1602ZJ INCLUSE	1688
NOU		4MP	Speed Dome IP Exterior; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.5" Progressive Scan CMOS; 2560x1440/2048x1536/1920x1080 @ 25fps; Color: 0.005 Lux/F:1.6; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 25x; Zoom digital: 16x; Lentila: 4.8~120mm; Pan Manual Speed: 0.1° ~ 80°/s, Pan Preset Speed: 80°/s; Tilt Manual Speed: 0.1° ~ 80°/s,Tilt Preset Speed: 80°/s; Audio 1 IN/ 1 OUT;Alarma 1 IN/ 1 OUT; Distanța IR: 100m, ajustabila de zoom; IP67;Micro SD Slot; Ethernet 10/100; 12 VDC, PoE, Max.18W; Dimensiuni:Φ164.5×290 mm; Greutate:2kg SURSA 12VDC si SUPORT DS-1602ZJ INCLUSE	2015

DS-2DE7230IW-AE		2MP	Speed Dome IP Exterior cu IR; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.05 Lux/F:2.0; B&W: 0.01 Lux/F:1.6; ICR; Zoom optic: 30x; Zoom digital: 16x; Lentila: 4.3~129mm; Tilt: -15°~90°(Auto Flip); Pan Manual Speed: 0.1°~160°/s, Pan Preset Speed: 240°/s Tilt Manual Speed: 0.1°~120°/s, Tilt Preset Speed: 200°/s; Audio 1 IN/ 1 OUT; Alarma 2 IN/ 1 OUT; Distanța IR: 150m, ajustabilă de zoom; IP67; Micro SD Slot; Ethernet 10/100; 24VAC/High-PoE max.40W; Dimensiuni: Φ220×353.4mm; Greutate: 4.5kg SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	2796
DS-2DE7232IW-AE		2MP	Speed Dome IP Exterior cu IR; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.005 Lux/F:2.0; B&W: 0.001 Lux/F:1.6; ICR; Zoom optic: 30x; Zoom digital: 16x; Lentila: 4.8~153mm; Tilt: -15°~90°(Auto Flip); Pan Manual Speed: 0.1°~160°/s, Pan Preset Speed: 240°/s Tilt Manual Speed: 0.1°~120°/s, Tilt Preset Speed: 200°/s; Audio 1 IN/ 1 OUT; Alarma 2 IN/ 1 OUT; Distanța IR: 150m, ajustabilă de zoom; IP67; Micro SD Slot; Ethernet 10/100; 24VAC/High-PoE max.40W; Dimensiuni: Φ220×353.4mm; Greutate: 4.5kg SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	2824
DS-2DF8223I-AEL		2MP	Speed Dome IP Exterior cu IR - DarkFighter; True Day/Night, 3D DNR, 120db True WDR; 3D intelligent positioning; 1/1.9" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.002 Lux/F:1.5; B&W: 0.0002 Lux/F:1.5; ICR; Zoom optic: 23x; Zoom digital: 16x; Lentila: 5.9~135.7mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR: 200m, ajustabilă de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -30°C~+60°C; Standard: IP67, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibilă cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	4686
DS-2DF8225IX-AEL		2MP	Speed Dome IP Exterior cu IR - DarkFighter; True Day/Night, 3D DNR, 120db True WDR; 3D intelligent positioning; 1/1.9" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.002 Lux/F:1.5; B&W: 0.0002 Lux/F:1.5; ICR; Zoom optic: 25x; Zoom digital: 16x; Lentila: 5.7~142.5mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR: 200m, ajustabilă de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -40°C~+65°C; Standard: IP67, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibilă cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	4883
DS-2DF8236I-AEL		2MP	Speed Dome IP Exterior cu IR - DarkFighter; True Day/Night, 3D DNR, 120db True WDR; 3D intelligent positioning; 1/1.9" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.002 Lux/F:1.5; B&W: 0.0002 Lux/F:1.5; ICR; Zoom optic: 36x; Zoom digital: 16x; Lentila: 4.5~162mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR: 200m, ajustabilă de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -30°C~+60°C; Standard: IP67, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibilă cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	6247
DS-2DF8836I5V-AELW		8MP	Speed Dome IP Exterior cu IR; True Day/Night, 3D DNR, 120db True WDR; 3D intelligent positioning; 1/1.9" Progressive Scan CMOS; 4096x2160 @ 25fps; Color: 0.02 Lux/F:1.5; B&W: 0.002 Lux/F:1.5; ICR; Zoom optic: 36x; Zoom digital: 16x; Lentila: 6.2~202mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR: 500m, ajustabilă de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -40°C~+60°C; Standard: IP67, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibilă cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC și SUPORT DS-1602ZJ INCLUDE	17030

DS-2DF8836IX-AEL		8MP	Speed Dome IP Exterior cu IR; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 2/3" Progressive Scan CMOS; 4096x2160 @ 25fps; Color: 0.005 Lux/F:1.5; B&W: 0.0005 Lux/F:1.5; ICR; Zoom optic: 36x; Zoom digital: 16x; Lentila: 7.5~270mm; Pan Manual Speed: 0.1° ~ 210°/s, Pan Preset Speed: 280°/s; Tilt Manual Speed: 0.1° ~ 150°/s, Tilt Preset Speed: 250°/s Distanța IR: 200m, ajustabila de zoom; 3D DNR; HLC/BLC; ; Smart Tracking, Smart Defog, Smart Codec; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -40°C~+60°C; Standard: IP67, IK10; Alimentare: 24VAC / High-PoE max.60W; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC si SUPORT DS-1602ZJ INCLUDE	12638
DS-2DP1636Z-IX-D/235		2MP	Camera Panoramica: 8 x 1/1.9" Progressive Scan CMOS; Rezolutia max. 2 × 4096 × 1800@ 30 fps; Unghi vizualizare orizontala: 360°/ verticala: 78°; Color:0.005 Lux @(F1.8,AGC ON); B/W:0.0005 Lux @(F1.8,AGC ON) SpeedDome: Suporta manual-tracking & auto-tracking; 1/1.9" Progressive Scan CMOS; Rezolutia max. 1920 × 1080 @ 30 fps; Color:0.002 Lux @(F1.5,AGC ON); B/W:0.0002 Lux @(F1.5,AGC ON); Zoom optic 36x, Zoom digital 16x; 360° endless pan range; -15 to 90° tilt range; 540°/s Pan Preset Speed; 400°/s Tilt Preset Speed; 0.1°to 300°/s Manual Pan Speed; 0.1°to 240°/s Manual Tilt Speed; 300 Presets programmable; preset image-freeze capability; 8 Patrols, up to 32 presets per patrol; Power-off Memory: Restores PTZ & lens status after reboot	25559
DS-2DY9187-AI8		2MP	Sistem de pozitionare Laser IR; True Day/Night, 3D DNR, Digital WDR; 3D intelligent positioning; 1/2.8" Progressive Scan CMOS; 1920x1080 @ 25fps; Color: 0.05 Lux/F:2.0; B&W: 0.01 Lux/F:1.6; ICR; Zoom optic: 32x; Zoom digital: 16x; Lentila: 8~250mm; Tilt: +40°~90°; Pan Manual Speed: 0.1°~100°/s, Tilt Manual Speed: 0.1°~40°/s; Audio 1 IN/ 1 OUT; Alarma 7 IN/ 2 OUT; Distanța IR: 800m, ajustabila de zoom; IP67; Micro SD Slot; Ethernet 10/100; 24VAC max.90W; Dimensiuni: 251×508x360 mm; Greutate:20kg	19637
DS-2PT3326IZ-DE3		2MP	Camera Panoramica: 3 x 1/2.8" Progressive Scan CMOS; Rezolutia max. 3 × 1920 × 1080@ 30 fps; Unghi vizualizare orizontala: 130°; Color:0.01 Lux @(F1.6,AGC ON); B/W:0.05 Lux @(F1.6,AGC ON) Speed Dome: 1/2.8" progressive scan CMOS; Rezolutie 1920×1080 @30fps;Zoom optic 4x; Lentila:2.8-12mm; Unghi vizualizare orizontala: 119°-61°; Color:0.01 Lux @(F1.6,AGC ON); B/W:0.05 Lux @(F1.6,AGC ON)	2129
DS-2TD4136D-50		2MP	Speed Dome IP Thermal + Optical Bi-spectrum; Thermal Vanadium Oxide Uncooled Focal Plane 384x288; Lentila 50mm; Detectie vehicule 3km, persoane 1km; CMOS; 1920x1080 @ 25fps; Zoom optic: 30x; Lentila: 4.3~129mm; Pan Manual Speed: 0.1° ~ 160°/s, Pan Preset Speed: 240°/s; Tilt Manual Speed: 0.1° ~ 120°/s, Tilt Preset Speed: 200°/s Distanța IR: 150m, ajustabila de zoom; 3D DNR; HLC/BLC; IP67; Micro SD Slot; Ethernet 10/100; BNC; RS-485; Audio: 1IN/1OUT; Alarma: 7IN/2OUT; Temperatura de operare: -40°C~+60°C; Standard: IP67; Alimentare: 24VAC max.60W; Compatibila cu standardul ONVIF, PSIA, CGI, ISAPI SURSA 24VAC si SUPORT DS-1602ZJ INCLUDE	28390
DS-6901UDI			Decoder H.264/MPEG4; Capacitatea de decodare: 4-ch@12MP, 8-ch@8MP, 12-ch@5MP, 20-ch@3MP, 32-ch@1080p; Iesiri: HDMIx4, CVBSx2(DB15), Audiox4(DB15); Intrari: 1xVGA; 1xDVI-I; Retea: 4x10/100/1000Mbps, 16x4x10/100Mbps; 1xRS-232(RJ45); 1xRS-485; Alarma:8IN/8OUT	2651
DS-6904UDI			Decoder H.264/MPEG4; Capacitatea de decodare: 4-ch@12MP, 8-ch@8MP, 12-ch@5MP, 20-ch@3MP, 32-ch@1080p; Iesiri: HDMIx4, CVBSx2(DB15), Audiox4(DB15); Intrari: 1xVGA; 1xDVI-I; Retea: 4x10/100/1000Mbps, 16x4x10/100Mbps; 1xRS-232(RJ45); 1xRS-485; Alarma:8IN/8OUT	5111
DS-6908UDI			Decoder H.264/MPEG4; Capacitatea de decodare: 8-ch@12MP, 16-ch@8MP, 24-ch@5MP, 40-ch@3MP, 64-ch@1080p; Iesiri: HDMIx8, CVBSx4(DB 15), Audiox8(DB15); Intrari: 1xVGA; 1xDVI-I; Retea: 4x10/100/1000Mbps, 16x4x10/100Mbps; 1xRS-232(RJ45); 1xRS-485; Alarma:8IN/8OUT	7880
DS-6916UDI			Decoder H.264/MPEG4; Capacitatea de decodare: 8-ch@12MP, 16-ch@8MP, 24-ch@5MP, 40-ch@3MP, 64-ch@1080p; Iesiri: HDMIx8, CVBSx4(DB 15), Audiox8(DB15); Intrari: 1xVGA; 1xDVI-I; Retea: 4x10/100/1000Mbps, 16x4x10/100Mbps; 1xRS-232(RJ45); 1xRS-485; Alarma:8IN/8OUT	12348

DS-7604NI-K1			Network Video Recorder; 4 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,4-ch@1080P; 1 HDD Port SATA/6TB; 2 USB2.0; 1 RJ45 10M/100M/1000M Ethernet; Alimentare: 12VDC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 260(W)x225(D)x48(H)mm; Greutate: 1Kg	325
DS-7604NI-K1/4PoE			Network Video Recorder; 4 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,4-ch@1080P; 1 HDD Port SATA/6TB; 2 USB2.0; 1 RJ45 10M/100M/1000M Ethernet; switch 4 porturi PoE integrat(40W) ; Alimentare: 48VDC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 315(W)x240(D)x48(H)mm; Greutate: 1Kg	480
DS-7608NI-K2			Network Video Recorder; 8 Ch IP Video, 1 IN/1 OUT Ch Audio, 4 IN/1OUT Alarma; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,8-ch@1080P; 2 HDD Port SATA/6TB; 1 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; Alimentare: 12VDC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 385(W)x315(D)x52(H)mm; Greutate: 3Kg	547
DS-7608NI-K2/8PoE			Network Video Recorder; 8 Ch IP Video, 1 IN/1 OUT Ch Audio, 4 IN/1OUT Alarma; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,8-ch@1080P; 2 HDD Port SATA/6TB; 1 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 8 porturi PoE integrat(120W) ; Alimentare: 220V; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 385(W)x315(D)x52(H)mm; Greutate: 3Kg	836
DS-7616NI-K2			Network Video Recorder; 16 Ch IP Video, 1 IN/1 OUT Ch Audio, 4 IN/1OUT Alarma; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,8-ch@1080P; 2 HDD Port SATA/6TB; 1 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; Alimentare: 12VDC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 385(W)x315(D)x52(H)mm; Greutate: 1Kg	552
DS-7616NI-K2/16PoE			Network Video Recorder; 16 Ch IP Video, 1 IN/1 OUT Ch Audio, 4 IN/1OUT Alarma; Iesiri Video: HDMI, VGA; Rezolutie HDMI:4K(3840x2160) / VGA: 1920x1080P; Compresie: H.265/H.264/H.264+ ; Rezolutie inregistrare/redare: 8Mpx, 6MPx, 5MPx, 4MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; Redare Sincrona:2-ch@4K,8-ch@1080P; 2 HDD Port SATA/6TB; 1 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 16 porturi PoE integrat(200W) ; Alimentare: 220V; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 385(W)x315(D)x52(H)mm; Greutate: 3Kg	1078
DS-7716NI-I4			Network Video Recorder 4K panou frontal cu touch ; 16 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 4-ch @ 4K sau 16-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	1830

DS-7716NI-I4/16P		Network Video Recorder 4K panou frontal cu touch ; 16 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 4-ch @ 4K sau 16-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 16 porturi 10M/100M PoE (IEEE 802.3 af/at) integrat max.200W ; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	2256
DS-7716NI-K4		Network Video Recorder 4K panou frontal cu touch ; 16 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 2-ch @ 4K/8-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	993
DS-7716NI-K4/16P		Network Video Recorder 4K panou frontal cu touch ; 16 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 2-ch @ 4K/8-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 16 porturi 10M/100M PoE (IEEE 802.3 af/at) integrat max.200W ; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	1461
DS-7732NI-I4		Network Video Recorder 4K panou frontal cu touch ; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 4-ch @ 4K sau 16-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	2043
DS-7732NI-I4/16P		Network Video Recorder 4K panou frontal cu touch ; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 4-ch @ 4K sau 16-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 16 porturi 10M/100M PoE (IEEE 802.3 af/at) integrat max.200W ; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	2626
DS-7732NI-K4		Network Video Recorder 4K panou frontal cu touch ; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 2-ch @ 4K/8-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	1348
DS-7732NI-K4/16P		Network Video Recorder 4K panou frontal cu touch ; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 × 2160)/60Hz , 4K (3840 × 2160)/30Hz, 1920x1080P; Rezolutie inregistrare/redare: 8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF ; Decodare: 2-ch @ 4K/8-ch @ 1080p ; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 1 RJ45 10M/100M/1000M Ethernet; switch 16 porturi 10M/100M PoE (IEEE 802.3 af/at) integrat max.200W ; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x390(D)x70(H)mm; 19-inch rack-mounted 1,5U; Greutate: 5Kg;	1788

DS-96128NI-I16			Network Video Recorder; 128 Ch IP Video , 1 IN/1 OUT Ch Audio; Iesiri Video: HDMIx2, VGA; Rezolutie HDMI / VGA: 1920x1080P; Rezolutie inregistrare/redare: 12Mpx, 8MPx, 6MPx, 5MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; 16 HDD Port SATA/8TB; 1 miniSAS; 16 IN/8 OUT Ch Alarma; 2 USB2.0; 2 USB3.0; 4 RJ45 10M/100M/1000M Ethernet; Interfata fibra optica 4 1000 Mbps; 1 RS-485; 1 RS-232; Alimentare: 100~240VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 442(D)x494(W)x146(H)mm; 19" standard 4U pentru montare rack; Greutate: 15.5Kg	15127
DS-96128NI-I24H			Network Video Recorder; 128 Ch IP cu Video wall management, HDMI output/input 6/1, pentru 48-ch@1080p , 1 IN/1 OUT Ch Audio; Iesiri Video: HDMIx2, VGA; Rezolutie HDMI / VGA: 1920x1080P; Rezolutie inregistrare/redare: 12Mpx, 8MPx, 6MPx, 5MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; 24 HDD Port SATA/8TB; 1 miniSAS; 16 IN/8 OUT Ch Alarma; 2 USB2.0; 2 USB3.0; 4 RJ45 10M/100M/1000M Ethernet; Interfata fibra optica 4 1000 Mbps; 1 RS-485; 1 RS-232; Alimentare: 100~240VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 442(D)x494(W)x146(H)mm; 19" standard 4U pentru montare rack; Greutate: 15.5Kg	27547
DS-96256NI-I24			Network Video Recorder; 256 Ch IP Video , 1 IN/1 OUT Ch Audio; Iesiri Video: HDMIx2, VGA, MAIN; Rezolutie HDMI / VGA: 1920x1080P; Rezolutie inregistrare/redare: 12Mpx, 8MPx, 5MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; 24 HDD Port SATA/8TB; 1 e-SATA; 16 IN/8 OUT Ch Alarma; 2 USB2.0; 4 RJ45 10M/100M/1000M Ethernet; Interfata fibra optica 4 1000 Mbps; 1 RS-485; 1 RS-232; Alimentare: 100~240VAC/6.3A; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 442(D)x494(W)x146(H)mm; 19" standard 3U pentru montare rack; Greutate: 22.86Kg	25459
DS-96256NI-I24H			Network Video Recorder; 256 Ch IP Video cu Video wall management, HDMI output/input 6/1, pentru 48-ch@1080p , 1 IN/1 OUT Ch Audio; Iesiri Video: HDMIx2, VGA, MAIN; Rezolutie HDMI / VGA: 1920x1080P; Rezolutie inregistrare/redare: 12Mpx, 8MPx, 5MPx, 3MPx, 1080P, UXGA, 720P, VGA, 4CIF, DCIF, 2CIF, CIF, QCIF; 24 HDD Port SATA/8TB; 1 e-SATA; 16 IN/8 OUT Ch Alarma; 2 USB2.0; 4 RJ45 10M/100M/1000M Ethernet; Interfata fibra optica 4 1000 Mbps; 1 RS-485; 1 RS-232; Alimentare: 100~240VAC/6.3A; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 442(D)x494(W)x146(H)mm; 19" standard 3U pentru montare rack; Greutate: 22.86Kg	31466
DS-9632NI-I8			Network Video Recorder 4K; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz; VGA1: 2K (2560 × 1440)/60Hz; HDMI2 / VGA2: 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/ UXGA/ 720p/ VGA/4CIF/DCIF/ 2CIF/CIF/QCIF; Decodare: 4-ch @ 4K sau 16-ch @ 1080p; Redare Sincrona: 16 Ch; 8 HDD Port SATA/6TB; RAID0, RAID1, RAID5, RAID10; 1 e-SATA; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x470(D)x90(H)mm; 19-inch rack-mounted 2U; Greutate: 10Kg	4614
DS-9664NI-I8			Network Video Recorder 4K; 64 Ch IP Video, 1 IN/1 OUT Ch Audio; Iesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz; VGA1: 2K (2560 × 1440)/60Hz; HDMI2 / VGA2: 1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/ UXGA/ 720p/ VGA/4CIF/DCIF/ 2CIF/CIF/QCIF; Decodare: 4-ch @ 4K sau 16-ch @ 1080p; Redare Sincrona: 16 Ch; 8 HDD Port SATA/6TB; RAID0, RAID1, RAID5, RAID10; 1 e-SATA; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x470(D)x90(H)mm; 19-inch rack-mounted 2U; Greutate: 10Kg	6531
iDS-2CD6412FWD/C			Intelligence network camera ; 1/3" Progressive Scan CMOS; Rezolutie: 1.3MP; Day/Night, WDR 120db, BLC, 3D DNR; ROI; 0.028Lux/F:2.0, AGC ON; Compresie video: H.264, MJPEG; Lentila fixa: 2,8 mm; Audio 1 In / 1 Out, Alarm 1 In / 1 Out; Frame: 25fps(1280x960), 25fps(1280x720); Detectie miscare, Tamper; Posibilitate stocare pe card SD/SDHC,NAS; 1 RJ45 10M/100M Ethernet; Temperatura de operare: -30°C~+60°C; Alimentare: 12VDC; Cablu 8m; Standard: ONVIF, PSIA, CGI Functia de "People Counting" se poate realiza folosind card SD, NVR, IVMS5200	1987

NOU			DeepinMind Network Video Recorder 4K; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; lesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz;VGA1: 2K (2560 × 1440)/60Hz; HDMI2 / VGA2:1920x1080P; Rezolutie inregistrare/redare: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/ UXGA/ 720p/ VGA/4CIF/DCIF/ 2CIF/CIF/QCIF; Decodare:4-ch @ 4K sau 16-ch @ 1080p; Redare Sincrona: 16 Ch; 8 HDD Port SATA/6TB; RAID0, RAID1, RAID5, RAID10; 1 e-SATA; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare: 220VAC; Temperatura: -10°C~+55°C; Umiditate: 10%~90%; Dimensiuni: 445(W)x470(D)x90(H)mm; 19-inch rack-mounted 2U; Greutate: 10Kg	11004

MONITORE & HDD-URI

PRODUS	IMAGINE		DESCRIERE PRODUS	#VALUE!
HDD WESTERN				0
WD10PURZ			Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 64MB; Capacitate: 1TB	297
WD20PURZ			Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 64MB; Capacitate: 2TB	410
WD40PURZ			Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 64MB; Capacitate: 4TB	652
WD60PURZ			Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 128MB; Capacitate: 6TB	1064
WD80PURZ			Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 128MB; Capacitate: 8TB	1390
Monitoare LCD /				0
PMCL624			Monitor color PELCO, 24", LED; HDMI, DVI, VGA, BNC, Audio IN-mini jack, Difuzor: x2 / 3W; Rezolutie max.: 1920x1080; Timp raspuns: 5ms; Contrast: 1000:1; 250cd/m²; Frecventa: H=15~75kHz, V:25~75Hz; Unghi: H=170°, V=160°; OSD; Alimentare: AC 100~240V; Dimensiuni: 21.3(D)x56.9(W)x42.9(H)cm, Se poate monta pe perete(suport neinclus); Greutate: 7.2Kg	2555
PMCL632			Monitor color PELCO, 32", LCD; HDMI, DVI, VGA, BNC, Audio IN-mini jack, Difuzor: x2 / 6W; Rezolutie max.: 1920x1080; Timp raspuns: 6.5ms; Contrast: 3000:1; 350cd/m²; Frecventa: H=15~75kHz, V:25~75Hz; Unghi: H=178°, V=178°; OSD; Alimentare: AC 100~240V; Dimensiuni: 7.67(D)x74.52(W)x43.94(H)cm, Se poate monta pe perete(suport neinclus); Greutate: 12.5Kg	3549
PMCL655			Monitor color PELCO, 55", LED; HDMI, DVI, VGA, BNC, Audio IN-mini jack, Difuzor: x2 / 3W; Rezolutie max.: 1920x1080; Timp raspuns: 5ms; Contrast: 1000:1; 250cd/m²; Frecventa: H=15~75kHz, V:25~75Hz; Unghi: H=170°, V=160°; OSD; Alimentare: AC 100~240V; Dimensiuni: 21.3(D)x56.9(W)x42.9(H)cm, Se poate monta pe perete(suport neinclus); Greutate: 7.2Kg	9030
DS-D5019QE-B			Monitor color HIKVISION, 18.5", LED-Backlit TFT LCD; HDMI, VGA; Rezolutie max.: 1366x768; Timp raspuns: 5ms; Contrast: 600:1; 200cd/m²; Unghi: H=90°, V=66°; OSD; Alimentare: AC 100~240V; Dimensiuni: 445.58mm*274.99mm*44.6mm; VESA 75mm x 75mm; Greutate: 2.8Kg	442
DS-D5022FC			Monitor color HIKVISION, 21.5", LED-Backlit TFT LCD; HDMI, VGA; Rezolutie max.: 1920x1080; Timp raspuns: 5ms; Contrast: 1000:1; 250cd/m²; Unghi: H=170°, V=160°; OSD; HDMIx1; VGAX1;BNC: INx1, OUTx1; USBx1; Audio 1IN/1OUT; Difuzor:2x2W; Alimentare: AC 100~240V; Dimensiuni: 511mm*313mm*45mm; VESA 100mm x 100mm; Greutate: 3.2Kg	652
DS-D5024FC			Monitor color HIKVISION, 23.6", LED-Backlit TFT LCD; HDMI, VGA; Rezolutie max.: 1920x1080; Timp raspuns: 5ms; Contrast: 1000:1; 250cd/m²; Unghi: H=170°, V=160°; OSD; HDMIx1; VGAX1;BNC: INx1, OUTx1; Audio 1IN/1OUT; Difuzor:2x2W; Alimentare: AC 100~240V; Dimensiuni: 561mm*339mm*45mm; VESA 100mm x 100mm; Greutate: 5.1Kg	765
X41T			Monitor de test Analog/HD-TVI 7" LCD; Rezolutie maxima 1920x1080P; Intrari CVBS/HDMI/VGA; Analog/HD-TVI 720P/1080P; Up the Coax (HIKVISION-C protocol); 3xBaterie Li-Ion; lesire 12V/2A pentru alimentarea camerelor; Dimensiuni: 205 x 155 x 38mm	1135

VIDEOINTERFONIE

VIDEOINTERFOANE IP - POST EXTERIOR				0
DS-KD8102-V			Post exterior, ABS, 3.5" Capacitive Touch Key, Display color incorporat 3.5-inch TFT LCD, display resolution: 480 * 320, Camera resolution: HD720P, 25fps(P), 10M/100M/1000M Self-adaptive Ethernet, Cititor card incorporat, Wiegand & RS-485, 8-ch alarm input, 4-ch alarm output, IP65, USB 2.0, 12 VDC, Visible Light Supplement	1404
DS-KD8002-VM			Post exterior, Aliaj Aluminiu, 3.5" Physical Touch Key, Display color incorporat 3.5-inch TFT LCD, display resolution: 480 * 320, Camera resolution: HD720P, 25fps(P), 10M/100M/1000M Self-adaptive Ethernet, Cititor card incorporat, Wiegand & RS-485, 8-ch alarm input, 4-ch alarm output, IP65, USB 2.0, 12 VDC, Visible Light Supplement	1745
DS-KV8102-IM			Post exterior, Aliaj Aluminiu, Camera resolution: HD720P, 25fps(P), 10M/100M Self-adaptive Ethernet, Cititor card incorporat, RS-485, 4-ch alarm input, 1-ch alarm output, IP65, 12 VDC, 1-Buton acces, IR Supplement	615
DS-KV8202-IM			Post exterior, Aliaj Aluminiu, Camera resolution: HD720P, 25fps(P), 10M/100M Self-adaptive Ethernet, Cititor card incorporat, RS-485, 4-ch alarm input, 1-ch alarm output, IP65, 12 VDC, 2-Butoane acces, IR Supplement	609
DS-KV8402-IM			Post exterior, Aliaj Aluminiu, Camera resolution: HD720P, 25fps(P), 10M/100M Self-adaptive Ethernet, Cititor card incorporat, RS-485, 4-ch alarm input, 1-ch alarm output, IP65, 12 VDC, 4-Butoane acces, IR Supplement	694
DS-KV8102-IP			Post exterior, ABS, Camera resolution: HD720P, 25fps(P), 10M/100M Self-adaptive Ethernet, Cititor card incorporat, RS-485, 4-ch alarm input, 1-ch alarm output, IP65, 12 VDC, 1-Buton acces, IR Supplement	425
DS-KB8112-IM			Post exterior, Aliaj Aluminiu, Camera resolution: HD720P, 25fps(P), 10M/100M Self-adaptive Ethernet, 1-ch alarm input, 1-ch alarm output, IP66, IK9, 12 VDC/PoE 12W, 1-Buton acces, IR 5m	425
VIDEOINTERFOANE IP - POST INTERIOR				0
DS-KH8301-WT			Post interior, camera frontala incorporata 0.3MP, 7" Touch-Screen, Mechanical Switch, TFT LCD color 7-inch, display resolution: 1024 * 600, Camera resolution: 640 * 480, 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n, 8-ch alarm input, support SD card, Power Over Network Cable/ 12 VDC	751
DS-KH6310-WL			Post interior, 7" Touch-Screen, TFT LCD color 7-inch, display resolution: 800 * 480, 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n, 2-ch alarm input, Power Over Network Cable/ 12 VDC	439
KIT VIDEOINTERFONIE ANALOGICA				0
DS-KIS202			Kit videointerfonie analogica 4 fire; Post exterior aluminiu cu releu senzor 1/4" CMOS(720x576), IR 2m; Post interior TFT LCD 7" (800x480); Comunicare 4 fire; Alimentare post exterior din monitor	481

ACCESORII

Keyboard				0
DS-1005KI			Controller USB pentru IVMS; 3D PTZ; joystick; Alimentare si comunicare prin USB; 15 butoane programabile; SO Window XP/7/8/8.1, USB 2.0, DirectX; Temperatura operare: -10°C~+55°C; Dimensiune: 167x177.5x116mm	865
DS-1006KI			Controller 4 axe; DVR; PTZ; VideoWall; Matrice; Ecran 128x64px; 1 RS-485; 1 RS-232; 1 RS-422; Alimentare: DC 12V/4.5W; Temperatura operare: -10°C~+55°C; Dimensiune: 435x193x110mm; Greutate: 1Kg	993
DS-1100KI			Controller IP; 3 axe; Controleaza pana la 256 echipamente IP; 7" TFT touch screen la 800x480; Audio 1IN/1OUT; 1 RS-485; 1 RS-232; 1 USB2.0; Alimentare: DC 12V/15W; Temperatura operare: -10°C~+55°C; Dimensiune: 110x193x435mm; Greutate: 2Kg	3952
DS-1600KI			Controller IP; 4 axe; Controleaza pana la 2000 echipamente IP; 10.1" TFT touch screen la 1024x600; 1 HDMI; 1 DVI; Audio 1IN/1OUT; 1 RS-485; 1 RS-232; 2 USB2.0; Alimentare: PoE, DC 12V/15W; Temperatura operare: -10°C~+55°C; Dimensiune: 404 x 180 x 163 mm; Greutate: 1.70Kg	4535
Lentile Megapixel				0
TV2712D-MPIR			Lentila varifocala; Megapixel; 2.7~12mm/F:1.2; DC Auto-iris; Corectie IR	567
Switch-uri				0
DS-3E0105P-E			Switch 5 porturi(4xPoE+1UPLINK) 10/100Mb/s, 4 porturi PoE IEEE802.3af @15.4W sau IEEE802.3at @30W, Buget PoE max. 58W, Extend On: 250 m @10M/ CAT 5e , 1 port UPLINK 100M, Sursa inclusa 51VDC/63W max, W132xH27.6xD93.3	183

DS-3E1310P-E		Switch 10 porturi(8xPoE 10/100Mb/s + 2xUPLINK 10/100/1000Mb/s) + 2 x 1000M SFP , 8 porturi PoE IEEE802.3af @15.4W sau IEEE802.3at @30W, Buget PoE max. 123W, Extend On: 250 m @10M/ CAT 5e , 110-240VAC/127W max, W440xH43xD285	496
DS-3E1318P-E		Switch web-managed 18 porturi(16xPoE 10/100Mb/s + 2xUPLINK 10/100/1000Mb/s) + 2 x 1000M SFP, 16 porturi PoE IEEE802.3af @15.4W sau IEEE802.3at @30W, Buget PoE max. 230W, Extend On: 250 m @10M/ CAT 5e , 110-240VAC/250W max, W440xH43xD285	1106
DS-3E1326P-E		Switch 26 porturi(24xPoE 10/100Mb/s + 2xUPLINK 10/100/1000Mb/s) + 2 x 1000M SFP, 24 porturi PoE IEEE802.3af @15.4W sau IEEE802.3at @30W, Buget PoE max. 230W, Extend On: 250 m @10M/ CAT 5e , 110-240VAC/250W max, W440xH43xD285	1404
Accesorii montaj			0
DS-1250ZJ		Aparatoare de ploaie pentru camere dome; Dimensiuni:264.7x152x189.6 mm; Greutate: 200g	36
DS-1258ZJ		Suport ABS pentru camera dome; Dimensiuni:111x120x161.5mm; Greutate: 200g	30
DS-1259ZJ		Suport inclinat pentru camera dome; Dimensiuni:Φ111x39.2mm; Greutate: 200g	20
DS-1260ZJ		Doza conexiuni aluminiu pentru camera bullet; Dimensiuni: Φ88.5mm	61
DS-1273ZJ-130-TRL		Suport perete pentru seria DS-2CD23xx; Dimensiuni: 132x183.5x228.5mm; Greutate:870g	88
DS-1275ZJ		Adaptor montaj pe stalp; Aliaj de aluminiu; Greutatea: 1205g; Dimensiuni: 117x143x194mm	82
DS-1276ZJ		Adaptor montaj pe colt; Aliaj de aluminiu; Greutatea: 1950g; Dimensiuni: 126x105x250mm	72
DS-1280ZJ-DM18		Doza conexiuni aluminiu pentru seria DS-2CD21xx; Dimensiuni: Φ111x42mm; Greutate:150g	41
DS-1280ZJ-DM21		Doza conexiuni aluminiu pentru seria DS-2CD27xxF-I(S); Dimensiuni: Φ137x42mm; Greutate:250g	47
DS-1280ZJ-DM26		Doza conexiuni aluminiu pentru seria DS-2CD45xxFWD-IZ(H)(S); Dimensiuni: Φ165x65mm; Greutate:466g	45
DS-1280ZJ-M		Doza conexiuni aluminiu pentru camere; Dimensiuni: Ø157 x 51.5 x 185mm	84
DS-1280ZJ-S		Doza conexiuni aluminiu pentru camere; Dimensiuni: Ø137 x 53.4 x 164.8mm	80
DS-1280ZJ-XS		Doza conexiuni aluminiu pentru camere; Dimensiuni: Ø100 x 43.2 x 129mm	50
DS-1294ZJ		Suport ABS pentru camera dome; Dimensiuni: 230x80x130mm; Greutate: 450g	48
DS-1602ZJ		Suport speed dome de perete; Material; Aliaj de aluminiu; Greutatea: 1070g; Dimensiuni: 97x182x305mm	78
DS-1602ZJ-C		Suport speed dome de colt; Material; Aliaj de aluminiu; Greutatea: 2200g; Dimensiuni: 176.8x194x419.5mm	112
DS-1602ZJ-P		Suport speed dome de stalp; Material; Aliaj de aluminiu; Greutatea: 2200g; Dimensiuni: 117x194x310mm	115
DS-1618ZJ		Suport speed dome de perete; Material; Aliaj de aluminiu; Greutatea: 550g; Dimensiuni: 110x145x189mm	64
DS-1619ZJ		Suport speed dome gat de lebada; Material; Aliaj de aluminiu; Greutatea: 6426g; Dimensiuni: 455.2x130.4x841.5mm	240
DS-1660ZJ		Suport speed dome parapet; Material; Aliaj de aluminiu; Greutatea: 2900g; Dimensiuni: 180x950x800 mm	240
DS-1661ZJ		Suport speed dome tavan; Material; Aliaj de aluminiu; Greutatea: 600g; Dimensiuni: 116.5x200mm	92
DS-1662ZJ		Suport speed dome tavan; Material; Aliaj de aluminiu; Greutatea: 380g; Dimensiuni:116.5x500mm	98
DS-1663ZJ		Suport speed dome tavan; Material; Aliaj de aluminiu; Greutatea: 600g; Dimensiuni: 116.5x57mm	50
MD 01HB		Suport plastic pentru camera CCTV	4
MD 205		Suport metal pentru carcasa/camera	7
MD 210		Suport metal ptr. carcasa MD 606, 607	16
Surse si backup			0
DSA-12PFG-12FEU		Sursa alimentare AC 90-264V, DC 12V/1A ; short-circuit protection SCP, surge protection (AC input), overload protection OLP; LxWxH: 70 x 29.8 x 78.7 mm	21
PSC 12010		Sursa CCTV capsulata IP67 AC 90-264V, DC 12V/1A ; short-circuit protection SCP, surge protection (AC input), overload protection OLP; LxWxH: 50 x 48 x 25 mm	36
PSC 12015		Sursa CCTV capsulata IP67 AC 90-264V, DC 12V/1.5A ; short-circuit protection SCP, surge protection (AC input), overload protection OLP; LxWxH: 58 x 58 x 28 mm	43

PSCL 12030			Sursa CCTV capsulata IP67 AC 90-264V, DC 12V/3A ; short-circuit protection SCP, surge protection (AC input), overload protection OLP; LxWxH: 135 x 50 x 33 mm	64
PSCL 12050			Sursa CCTV capsulata IP67 AC 90-264V, DC 12V/5A ; short-circuit protection SCP, surge protection (AC input), overload protection OLP; LxWxH: 150 x 56 x 34 mm	89
PSDC05125T			Sursa 12V/5A cu 5 iesiri; Alimentare: 85÷264VAC; leșirea alimentării: 5 x 1A/12VDC; Intervalul de fixare a tensiunii: 12V÷15V; Randament: 80%; Elemente de siguranță: SCP, OLP, OVP; Dimensiuni: W=235 H=181 D=51+8 mm; Observații: carcasă murală, modul de închidere – prin înșurubare	183
PSDC08128T			Sursa 12V/8A cu 8 iesiri; Alimentare: 176÷264VAC; leșirea alimentării: 8x 1A/12VDC; Intervalul de fixare a tensiunii: 12V÷15V; Randament: 83%; Elemente de siguranță: SCP, OLP, OVP; Dimensiuni: W=295 H=246 D=51+8 mm; Observații: carcasă murală, modul de închidere – prin înșurubare	212
PSDC161216T			Sursa 12V/16A cu 16 iesiri; Alimentare: 176÷264VAC; leșirea alimentării: 16 x 1A/12VDC; Intervalul de fixare a tensiunii: 12V÷15V; Randament: 85%; Elemente de siguranță: SCP, OLP, OVP; Dimensiuni: W=295 H=246 D=51+8 mm; Observații: carcasă murală, modul de închidere – prin înșurubare	297
HPSB3512C			Sursa de tensiune neîntreruptibilă DC 13.8 V/3A (5 iesiri/1A), reglabila 12~14VDC; Sursa comutatie 176~264VAC; Protecție la suprasarcina, supratensiune, scurt-circuit, antisabotaj; Spatiu pentru acumulator de max. 12V/17Ah; Curent de incarcare acumulator 0,5A	197
PSDCB05125C			Sursa de tensiune neîntreruptibilă DC 13.8 V/5A (5 iesiri/1A), reglabila 11~13.8VDC; Sursa comutatie 176~264VAC; Protecție la suprasarcina, supratensiune, scurt-circuit, antisabotaj; Spatiu pentru acumulator de max. 12V/17Ah; Curent de incarcare acumulator 1 sau 2A	263
PSDCB09129C			Sursa de tensiune neîntreruptibilă DC 13.8 V/9A (9 iesiri/1A), reglabila 11~13.8VDC; Sursa comutatie 176~264VAC; Protecție la suprasarcina, supratensiune, scurt-circuit, antisabotaj; Spatiu pentru acumulator de max. 12V/17Ah; Curent de incarcare acumulator 1 sau 4A	304
AWO529W			Cutie metalica securizata, cu tamper si cheie pentru DVR; Dimensiuni interne: W=385, H=495, D=110, externe: W=435, H=500, D=130 [mm, +/-2] ; Dimensiuni raft intern DVR ajustabile: latime de la 145 mm la 345 mm / inaltime de la 40 mm la 100 mm	410
AWO530W			Cutie metalica securizata, cu tamper si cheie pentru DVR; Dimensiuni interne: W=490, H=630, D=110, externe: W=535, H=650, D=130 [mm, +/-2] ; Dimensiuni raft intern DVR ajustabile: latime de la 245 mm la 445 mm / inaltime de la 40 mm la 100 mm	510
Cablu				0
CAB 2x0.75			Cablu alimentare 2 fire, 2 x 0.75mm, Rola 100m	99
DS-1LC1SCA2C-200B			Cablu HIKVISION siamez, coaxial RG59(Oxygen Free Copper) 20AWG+ alimentare 2x0,5(Oxygen Free Copper), Flame retardant VW-1, Tambur 200m	497
DS-1LN5-ES			Cablu U/UTP Cat.5e, 4xAWG24, PVC, gri, cutie 305m, ISO/IEC11801,TIA-568-C.2	331
DS-1LN6-UU			Cablu U/UTP Cat.6, 4xAWG23, PVC, portocaliu, cutie 305m, ISO/IEC11801,TIA-568-C.2	439
MINICOAXIAL RG59			Cablu minicoaxial RG59 - AL, Rola 100m	77
Conectori si accesorii				0
BNC			Mufe BNC surub/regleta	3
BNC			Mufe BNC surub/lipire	3
BNC			Mufe BNC sertizare RG58	3
DS-1H18S/E			Set 2 bucati video balun pasiv HD 5/4/3/2 Mp, pigtail, Hikvision	26
DS-2FP2020			Microfon omnidirectional Hi-Fi pentru 70m2, sensibilitate -34dB, SNR 60dB (1m40 dB audio tone SPL) 40dB(10m 40 dB audio tone SPL)1KHz at 1 Pa, DC 12V (9V-15V)@25mA	126
M. ALIM			Mufe alimentare mama/tata	2
MD 104TP			Video balun pasiv 4 camere	71
ML 517			Adaptor alimentare mufa jack 12v la DIN4 (pentru DVR HIKVISION)	21
P-TR1HD			Set 2 bucati video balun pasiv HDTV/HDCVI/AHD cu surub	17
SDI01-2			Convertor HD-SDI (SDI -SMPTE 259M, HD-SDI -SMPTE 292M) la HDMI (tip A); Consum 750mA; Dimensiuni: 67 x 110 x 27 (mm); Greutate: 185g	510
SP 001			Protectie la descarcari electrice pe cablu coaxial ptr. CCTV, CATV cu BNC	43

TTA 111VT		Video balun activ; Transmisor (camera side); 1 camera; Tensiune alimentare DC 12V; Transmisie pina la 2.000 m impreuna cu TTA 111VHA; Protectie la supratensiuni	115
PIR, Buton panica, Contact			0
KIT NX-4		KIT Centrala 4 zone; Expandabila la 8 zone fir sau wireless; 1 partitie; Memorie pentru 512 evenimente; Comunicator(ID, SIA) pentru 3 numere de telefon; Suporta 8 tastaturi LED sau LCD; Include tastatura led NX108, cutie cu transformator de 40W, 1 pir IS215TCE, 1 contact magnetic, 1 sirena interior LD97	425
KIT C003-E1-K03		KIT Galaxy Flex 20 Centrala de efractie max. 20 zone (12 pe placa), max. 7 iesiri programabile (3 pe placa) si 3 partitii, sursa pe placa 1A si baterie backup de max. 10Ah; Comunicator linie telefonica PSTN incorporat; O magistrala RS-485 configuratie simplu / dublu daisy-chain max. 1000m ptr. module max. 4 tastaturi cu tastatura MK8 si cutie cu sursa	709
HO-02		Buton de panica cu contact NC/NO; Alb	4
HO-03A		Contact magnetic; Montaj aparent; Nepolarizat; Interspatiu: 5cm; NO/NC; Alb	10
KX15DTAM		Senzor PIR dubla tehnologie; Tehnologie BlueVawe; Compensare digitala a temperaturii; Detector volumetric; Sensibilitate ajustabila(AUTO/PC1) ; Raza maxima 15/18m;Rezistente EOL selectabile ; Viteza detectie 0.2-2.5m/s; Unghi acoperire 85°;Zone detectie 74;Planuri detectie 7;Grad 3 de securitate; Dimensiuni: 117x69x50 mm; Greutate: 125g	126
Acumulatori			0
ACUM 7Ah		GBS12705 Acumulator 12V/7,05Ah, 151 x 99 x 65mm, 1.90Kg	60
ACUM 17Ah		GBS12170 Acumulator 12V/17Ah; Dimensiuni: 181mm x 76 mm x 167 mm , 4,75 kg	169
ACCESORII VIDEOINTERFONIE			0
DS-KAB02		Doza montaj aplicat din otel inoxidabil pentru post exterior DS-KV8x02-IM	111
DS-KAB03-V		Doza montaj aplicat din otel inoxidabil pentru post exterior DS-KV8102-IP	283
DS-KAB21-H		Suport birou pentru posturile de interior seria KH63/83; Material din otel inoxidabil	82
DS-KAB86		Doza post exterior DS-KV8102-IP	13
DS-KAD606		Switch video/audio, built-in voltage-stabilized power, 8 x 100Mbps ports(6-ch supporting network cable powering and 2-chcascading LAN interfaces), 230VAC	352
DS-KAD606N		Switch video/audio, built-in voltage-stabilized power, 8 x 100Mbps ports(6-ch supporting network cable powering and 2-chcascading LAN interfaces), 24VDC Nu include sursa	121
DS-KAD606P		Switch video/audio, built-in voltage-stabilized power, 8 x 100Mbps ports(6-ch supporting network cable powering and 2-chcascading LAN interfaces), 24VDC Sursa 24VDC inclusa	247
DS-KAW50-1		Sursa alimentare Output: 12 VDC, 4.2A	111
MF-Y3(Red)		Distanta citire/scriere : 5 to 10cm ; Frecventa: 13.56MHz; IP67; Temperatura functionare: -10° C to +50° C	4
Software IVMS			0
IVMS5200-P16		Licenta software IVMS5200 Professional compatibil cu echipamentele IP Hikvision si cu echipamente IP ONVIF	993